

RETARDER PROVER - DC SERIES

SINMAG

REACH-IN RETARDER PROVER WITH ADJUSTABLE SHELVES

- Fully automatic from retarding to proving
- Four stage proving technique
- Fully stainless steel with 60mm-thick insulation
- One-door, one-chamber retarder prover reach-in model
- Large double-glazed window in door
- Stainless steel inside and out

Very compact and elegant design - quick and easy installation. Just connect power and water (no external compressor required)



Retarder-proofer with fixed shelves

Model		DC-36S	DC-36F	DC-18F	DC-236S
Capacity(number of trays)		36	36	18	36
Tray Size(mm)		400×600	460×720	460×720	400×600
Number of Shelves		18	18	18	18
Tray Layout					
Dimension(mm)	Width	775	1270	760	775
	Depth	1200	1060	1145	1880
	Height	2130	2135	2135	2130
Weight(kg)		190	240	180	250
Door		singel door	double door	single door	double door
Compressor Power(kw)		1.125	1.125	1.125	0.5×2 compressors
Heater Power(kw)		2.3	2.3	2	1.5×2 heaters
Control Mode		digital control panel	digital control panel	digital control panel	2 independent digital control panel
Temperature Range(°C)		2~40	2~40	2~40	2~~40
Outside Plate		stainless steel plate with 50mm PU insulation	stainless steel plate with 60mm PU insulation		stainless steel plate with 50mr PU insulation

Equipment supplies and 24/7 service to the baking industry

5 Blackman Cr, South Windsor, NSW, 2756, Australia

P: +61 2 8004 6105

www.bakewise.com.au

